
HAND TORQUE MULTIPLIERS



Bhartiya Torque Multipliers are heavy duty tools used to increase the Torque produced by Torque Wrenches. They have been developed to meet the high Torque requirements and keeping in view space restrictions in Torque Wrench applications. Torque multipliers are suggested for either tightening of high tensile bolts or loosening Rusty & Frozen but bolts.

FEATURES:



The multiplier has a gear mechanism by which the Torque applied on the input side is multiplied in a particular ratio. Bharatiya Torque Multipliers are available in Multiplication Factors of 5:1 & 25:1. Torque Multiplier covers Torque requirement from 100 kg mtr. To 925 kg mtr. (750 lb. Ft to 7000 lb.ft)

APPLICATIONS:

Bhartiya Tool Torque Wrenches are recommended to be used at the Input end to achieve an exactly calculated output Torque so the fluctuation of efficiency remains extremely small over period. It is extensively used in large Petrochemicals and Refineries.



SPECIFICATIONS

Hand Torque Model No.	Maximum Output Torque Lbft. Nm. Kgf.m.			Estimated Bolt Capacity (S. Quantity)		Multipl- ication Factor	Fe- male Input Sq.	Sq.	Major Dia Mm.	Depth	Torque Wrench No.	Approx. Weight with Reaction Plate Kg
						-					D.T.I.I. 2000	_
BM - 1	1250	1700	170	1 1/8	28	5	1/2	3/4	115	85	BTW - 3000	4.5
BM - 2	1250	1700	170	1 1/8	28	5	3/4	1	115	93	BTW - 3000	5.0
BM - 2/25	1250	1700	170	1 1/8	28	25	1/2	1	115	120	BTW - 3600	7.0
BM - 5	2000	2700	275	1 3/8	35	5	3/4	1	136	100	BTW - 5000	8.0
BM - 5/25	2000	2700	275	1 3/8	35	25	1/2	1	136	130	BTW - 1200	11.0
BM - 6	2500	3400	345	1 ½	38	5	3/4	1 ½	136	105	BTW - 8400	8.5
BM - 6/25	2500	3400	345	1 ½	38	25	1/2	1 ½	136	130	BTW - 1200	11.5
BM - 7	4500	6000	622	2 ½	62	5	3/4	1 ½	168	125	BTW - 12300	15.5
BM - 7/25	4500	6000	622	2 ½	62	25	1/2	1 ½	168	180	BTW - 3000	19.5
BM - 9/25	7000	9500	965	3	75	25	3/4	1 ½	220	170	BTW- 5000	27.0