### **SPRING BALANCER:**

## BSEW Series



These balancers are provisioned with wire arrest mechanism, which locks the drum pulley in case of tool disengagement. These balancers are available for capacity from 9 - 70 Kg. & have all the feature of BSWF balancers as well. These balancers are primarily used with welding guns and applications where chances of wireslitting or tool disengagement due to accidental failure are higher.

BHARTIYA Spring Balancer is a safe and completely reliable means of suspending working tools: Portable Hand Tools, Welding Guns, Spray Guns, Shot Blast Guns, Drifting Attachments in Mines and Quarries, Jute and Synthetic Bag Closing Machines Etc.

#### **FEATURES:**

- Quick Installations
- Heavy Duty Spring
- Easy Tension Adjustment- No tools required
- Durable Nylon covered steel rope
- Convenient Snap type tool clip
- Inline alignment of Hanger & Tool Hook
- Ergonomic Design User Friendly



CAPACITY	MODEL	WEIGHT	TRAVEL	CAPACITY	MODEL	WEIGHT	TRAVEL
Kg	NO.	kg	Meter	Kg	NO.	Kg	Meter
9.0 - 15.0	BSEW - 15	5.0	1.3	9.0 - 15.0	BSEW - 15 L	10.0	2.3
15.0 - 22.0	BSEW - 22	9.5	1.5	15.0 - 22.0	BSEW- 22 L	10.0	2.3
22.0 - 30.0	BSEW - 30	10.0	1.5	22.0 - 30.0	BSEW - 30 L	11.0	2.3
30.0 - 40.0	BSEW - 40	12.5	1.5	30.0 - 40.0	BSEW - 40 L	14.5	2.3
40.0 - 50.0	BSEW - 60	13.0	1.5	40.0 - 50.0	BSEW- 60 L	15.0	2.3
50.0 - 60.0	BSEW - 60	13.5	1.5	50.0 - 60.0	BSEW - 60 L	16.0	2.3
60.0 - 70.0	BSEW - 70	14.0	1.5	60.0 - 70.0	BSEW - 70 L	16.5	2.3

# **BHARTIYA INDUSTRIES**

WORKS: PLOT NO. 268, DIGVIJAY INDUSTRIAL ESTATE NO.2, UPAVAN, POKHARAN ROAD NO.1, THANE (W) M.S., INDIA - 400603 OFFICE: G-201, USHA COMPLEX, KHANDELWAL MARG, BHANDUP (W.), MUMBAI -400078, INDIA

PH.: +91-22-2585 4509, 90290 05461 FAX: +91-22-2588 3527.

E-mail: bharatflex@yahoo.com

Website: www.bharatiyaindustries.com, www.tubecleaner.co.in

**Authorised Dealer** 

### **SPRING BALANCER:**



Closed Body Sheet Metal Spring Balancer

The range of spring balancer comprises of a sheet metal body housing a spring wound on a shaft with safe, protective, tensioning system.

#### FEATURES:

- Quick Installations
- Heavy Duty Spring
- Easy Tension Adjustment- No tools required
- Durable Nylon covered steel rope
- Convenient Snap type tool clip
- Inline alignment of Hanger & Tool Hook
- Ergonomic Design User Friendly



Model no.	Capacity (kg)	Cable Travel (Mtr.)	Diameter of Cable (mm)	Weight (Kg)
BSPC-3	1.0 to 3.0	1.5	2.8	1.5
BSPC-3L	1.0 to 3.0	2.5	2.8	1.7
BSPC-3.5L	2.5 to 3.5	3	2.5 PVC Nylon	1.7
BSPC-5	2.5 to 5.0	1,5	2.8	1.5
BSPC-5L	2.5 to 5.0	2.5	2.8	1.7

## **BHARTIYA INDUSTRIES**

WORKS: PLOT NO. 268, DIGVIJAY INDUSTRIAL ESTATE NO.2, UPAVAN, POKHARAN ROAD NO.1, THANE (W) M.S., INDIA - 400603 OFFICE: G-201, USHA COMPLEX, KHANDELWAL MARG, BHANDUP (W.), MUMBAI -400078, INDIA

PH.: +91-22-2585 4509, 90290 05461 FAX: +91-22-2588 3527.

E-mail: bharatflex@yahoo.com

Website: www.bharatiyaindustries.com, www.tubecleaner.co.in

**Authorised Dealer**